




KRS RANGE



A premium transport solution, the KRS low profile system is designed to blend into bus designs to enhance vehicle appearance. For maximum flexibility and weight distribution, the design configurations enable the unit to be installed anywhere on the roof of the bus. Eliminating the need for floor heaters, the KRS heat function can provide all temperature control needs in one unit. While low profile, this system maintains Thermo King's reputation for high performance and low maintenance costs.



THERMO KING

 07 3712 7777

 www.qtk.com.au

 info@qtk.com.au

KEY FEATURES

- Powerful performance to suit all Australian conditions
- Excellent pulldown, reheat and de-humidification
- Low profile roof mounted unit
- High strength, ultra light two piece aluminium frame
- Quality condenser for high ambient operation

SPECIFICATIONS

Description	KRS Brushless	KRS Tropical
Rated Heated Capacity (kW)	34	30
Max Cooling Capacity (kW)	35	42
Rated Cooling Capacity (kW)	29	36
Evaporative Air Flow (m ³ /h)	5,100	5,100
Refrigerant	R134a	R407c
Weight (kg)	188	210
Dimensions (L*W*H, mm)	4287*1827*181	4274*1900*181
Voltage (V)	27	27
Current (A)	87	107

**Maximum rated and cooling capacities are calculated using the X430 Compressor*



QTK Group is invested in supporting our customers on the journey to achieve more sustainable transport solutions. Working closely with Thermo King engineers, using high-quality components and intelligent design to produce efficient HVAC equipment.

